



## TB24 24 Fibre Lockable Outdoor FTTH Termination Box

A robust ABS IP65 termination box designed to manage up to 24 terminated fibres. This box can house up to 6 SC duplex or LC Quad adaptors. It has an internal detachable tray with bend radius protection, integrated cable tie points, 2 cable exit points and 1 cable entry point which maintain the IP65 rating. It is suitable for both indoor and outdoor wall mounted applications.

### Features

- Up to 24 fibres
- Available with 6 LC Quad or SC Duplex adaptors
- Compatible with PLC splitters
- Wall mounted
- IP65 rated for outdoor use
- Lockable door for enhanced security
- Detachable tray with integrated bend radius control
- Integrated cable tie points for securing incoming cable
- Sealing glands for up to 2 exiting + 1 incoming cable
- ROHS, REACH and SvHC compliant


### Applications

- FTTH
- Outdoor applications
- Telecommunication networks
- CATV
- Data communication networks
- Ethernet, Fibre Channel, ATM, LAN, MAN and WAN

## Specifications

ELEMENT	VALUE
Height	258mm
Width	186mm
Depth	61mm
Suitable for Adaptor Type	LC Quad, SC Duplex
Number of ports	6
Cable Entry	1
Cable Exit	2
Material	ABS
Operating Temperature	-40°C to +60°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754
Compliant to	RoHS, Reach/SVHC

## Ordering Information



### Example:

**CTB24-03-92-06** – TB24 Outdoor FTTH Termination Box Loaded With 6 SC/APC Duplex Adaptors  
**CTB24-XX-XX-UL** – TB24 Outdoor FTTH Termination Box Unloaded